































Modular Design, High Power, Multi-Application Highbays / Flood Light Lights

LEDG-050-FL-DLC	LEDG-100-FL-DLC	LEDG-150-FL-DLC	LEDG-200-FL-DLC	LEDG-250-FL-DLC	LEDG-300-FL-DLC	LEDG-400-FL-DLC
						
						
						
						



Ph: 732-741-9099 Fax: 732-741-8170 Toll Free: 866-LED-8493
 331 Newman Springs Road, Bld. 1, 4th Floor, Ste 143, Red Bank, NJ 07701

Visit our website at <http://www.ledgreen.com>

LEDGREEN offers high quality modular design with our industrial LED lighting that is built to provide years of outstanding and trouble free service. IP 67 rated LED outdoor Floods and High Bays that are UL and DLC listed. LED source is Philips-Lumileds LUXEON and Meanwell Drivers for durability and dependability. LED lifetime L70 - 70,000 hours with expected lifetime 100,000 hours. Extruded Aluminum Alloy heat sink, powder coated die cast aluminum frame and modular design for quick and convenient install and maintenance.

Model LEDG-	50	100	150	200	250	300	400	FL-DLC
Input Voltage	AC100-277V (347V/480V available)							
Power (watts)	50	100	150	200	250	300	400	
Mounting Options	Universal Hanging Bracket, Hanging Ring Mount, Pendant Mount							
Beam	60°, 120° Beam Angle							
Led Source	Philips-Lumileds LUXEON®							
Led Quantity (Bars=50 watts)	1	2	3	4	5	6	8	
Power factor	95%							
Lumen Output	5,000	10,000	15,000	20,000	25,000	30,000	40,000	
CRI	> 75							
Color temperature	4000k, 5000k, 5700k							
Fixture Material	Die-Cast Aluminum, PC							
PCB Surface	Conformal Coating							
IP Rating	IP 67							
Operating Temp.	-40 °C to +50 °C (-40 °F to 122 °F)							
Cooling System	Aluminum Heat Sinking, Open, Modular Design							
Driver	Meanwell (UL & CUL Approved) IP 67							
Lifespan	> 70,000 hours							
Application	Flood Light, High Bay, Multi-Usage							
Certifications	UL, DLC, CE, RoHS, POV, LM79, LM80							
Warranty	5 Years							
MH/HPS Replacement	125	250	400	500	600	750	1,000	

